


# ALICLAD MAX



## II VERTICAL II TIMBER BATTEN

HIGH PERFORMANCE ALUMINIUM  
WEATHERBOARD SYSTEM



MATERIALS • SYSTEMS • SOLUTIONS

# ALICLAD MAX

The Building Agency is the exclusive distributor of a cultivated selection of well-respected brand name cladding and roofing products and systems.

The Building Agency's focus is to ensure correct and comprehensive selections from our product and system ranges and to assist with design, specification and delivery of high performance buildings.

The Building Agency introduces our newly developed - Aliclad Max System

Performance and aesthetics find a perfect balance in the latest contemporary aluminium cladding system designed in New Zealand for our local conditions.

The tough New Zealand climate calls for exterior products that can perform in all weather conditions, meet the most stringent code and standards, and bring elegance and architectural integrity.

AliClad Max System, designed by The Building Agency, is a premium aluminium weatherboard system that has had every detail and feature designed, tuned and resolved. Backed by decades of local experience and international product knowledge, AliClad Max System offers architects, builders and developers a robust and beautifully finished product, supported on an easy-to-install fixing system engineered to perform.

Designed for large-scale commercial projects with a residential application.  
Designed for:

**WEATHER-TIGHTNESS:** The system has been designed in line with NZBC and been tested to be E2 via NZS4284:2008.

**STRUCTURE:** The AliClad Max System is designed for buildings in wind zones from Low to Extra High Wind loadings and engineered to be fixed at maximum span distances for easier application and reduced project costs.

**FIRE PROTECTION:** Aluminium is defined as non-combustible under the NZBC C clause and when correctly specified the support system forms a limited / non-combustible wall assembly. AliClad Max System is tested for buildings over 25m in total height by a full-scale system fire performance test to BR135 and BS8414.

**FINISH AND AESTHETICS:** Sublimated woodgrains, Flat and matt powdercoat options, Anodised, Anodised-look paint finishes, and horizontal and vertical profile alignments achieve both classic and contemporary designs with ease.

## TABLE OF CONTENTS

### AliClad Max - Horizontal - Alpha Rail

#### Information

AC-H-AR-CP - AliClad Max System Compliance Statement  
AC-H-AR-Apx.A.T2 - AliClad Max System Appendix A - Table 2 - Fixing  
Span Table

#### Profiles & Accessories

AC-H-AR-PL - AliClad Max System Parts List  
AC-H-AR-PRO-01 - AliClad Max System Cladding Profiles  
AC-H-AR-PRO-02 - AliClad Max System Trims Profiles  
AC-H-AR-MDS - AliClad Max System Mechanical Drainage System Parts

#### General Processing

AC-H-AR-GP-01 - Cut Board Terminations

#### TYPICAL DETAILS

##### 1. CORNERS

- 1.1. External Corner
- 1.2. Internal Corner
- 1.3. External Corner - Smaller Cladding Type
- 1.4. Internal Corner - Smaller Cladding Type

##### 2. VERTICAL JOINTS

- 2.1. Vertical Joint Typical
- 2.2. Vertical Joint Orientation Change
- 2.3. Vertical Joint Smaller Cladding Type
- 2.4. Vertical Joint Larger Cladding Type

##### 3. HORIZONTAL JOINTS

- 3.1. Typical Horizontal Joint
- 3.2. Interstorey Joint

##### 4. CLADDING TOP & BOTTOM

- 4.1. Top of Cladding/Parapet
- 4.2. Bottom of Cladding at Ground
- 4.4. Bottom of Cladding at Apron Roof
- 4.8. Barge to Soffit

##### 5. SOFFITS

- 5.1. Wall Below Soffit <90°
- 5.2. Wall Above Soffit <90°
- 5.6. Wall Below Flat Sheet Soffit <90°
- 5.8. Wall Below Flat Sheet Soffit >90°

##### 7. JOINERY

- 7.1. Residential Window Jamb - Recessed
- 7.2. Residential Window Head - Recessed
- 7.3. Residential Window Sill - Recessed
- 7.4. Residential Window Jamb - WANZ/Supported
- 7.5. Residential Window Head - WANZ/Supported
- 7.6. Residential Window Sill - WANZ/Supported

Detail List

Detail Number

AC-H-AR-DL.2

Version

JAN 2024 [v1.4]

# ALICLAD MAX

## COMPLIANCE STATEMENT

AliClad Max System is an extruded aluminium cladding system that can be installed horizontally or vertically, comprised of 2.2mm thick interlocking weatherboards in multiple design profile options and an accompanying flashing system. The system has been designed up to extra high wind zone in accordance with NZS3604 and engineered to be fixed at increased span distances to provide simple, strong, and safe installations.

This compliance statement covers **AliClad Max System** on 20mm Drained & Ventilated cavities.

Allowance must be made for unhindered thermal expansion and contraction. AliClad Max System weatherboards must be cut to length allowing

a 1 mm gap per metre of board and the fixing holes must be oversized to accommodate potential movement.

### NZBC Clause B1 Structure

B1.3.1, B1.3.2, B1.3.3(a,f,h,j,q), B1.3.4

AliClad Max System structural analysis was undertaken with capacities determined using and theoretical analysis. Span tables for 20mm cavities have been developed to determine the required cladding fixing, batten/rail fixing and screws to main structure fixing spacing.

The AliClad Max System cladding system has been designed to withstand up to

±2.40 kPa (ULS). When constructed in accordance with the structural and installation guidelines as per Appendix A, AliClad Max System will meet NZBC Clause B1.

### NZBC Clause E2 External Moisture

E2.3.2, E2.3.5, E2.3.7

AliClad Max System is intended to be part of a rainscreen cladding system where the panels form the outermost water shedding layer. The cladding line is expected to deflect most of the water hitting the façade. The weather resistant line is located at the back of the rainscreen cavity that is typically constructed with a flexible building wrap or rigid air barrier compliant with NZBC E2/AS1: Table 23.

Where water does penetrate the cladding line, the cavity between the cladding and the structural wall is expected to prevent water being able to migrate onto the structural wall and allow water to drain down. The cavity also allows ventilation which aids in the drying of any residual water and drying of the structural wall.

### NZBC C3 Fire Performance

C3.5, C3.6, C3.7a

AliClad Max System is manufactured from solid aluminium. As per MBIE Guidance (MBIE 2817 Fire Performance of External Wall Cladding Systems) that for buildings categorised as low risk (<10m high & >1m away from relevant boundary.) There are no requirements for fire testing protocols P1 to P5 and therefore all products are suitable for use in this application.

Where consideration of fire safety is required due to proximity of relevant boundaries, AliClad Max System can contribute to a building's performance when specified on one of the applicable non-combustible support systems available.

### NZBC Clause B2 Durability

B2.3.1b, B2.3.2

AliClad Max System material is 6063-T5 grade aluminium and by its nature is inherently durable. Aluminium is a reactive metal that quickly forms a stable oxide layer upon contact with the atmosphere which seals the raw aluminium from further oxidation. Therefore, aluminium is fundamentally durable. Aluminium supports are suitable to be used in all New Zealand exposure/atmospheric zones.

In addition, the AliClad Max System is finished using premium powder coating systems, applied locally.

#### Timber and Plastic Battens and Fixings

On Low-Risk buildings where fire requirements allow, a timber or HDPE cavity packer batten system may be used. Where timber is used it must be at a minimum of H3.1 treatment. If applicable a suitable bond breaker must be utilised to ensure no contact between cladding, flashings, and treated battens. Fixings for AliClad Max System must achieve >35mm structural embedment into main structure.

Refer to Appendix A Fixing Table 1

#### Aluminium Battens and Fixings

Cladding rails and fixings are also manufactured from aluminium and stainless steel, both materials are recognised as sufficiently durable and should remain serviceable throughout the expected serviceability of the cladding system. Fixings of aluminium rails must achieve >45mm embedment into main structure.

Refer to Appendix A Fixing Tables 2 & 4

#### Galvanised Support and Battens

To meet the durability requirements, mild steel support and battens need to be protected against corrosion. Support frames must have a minimum wall thickness of 1.15BMT. Support frames are to be coated with Zinalume steel AZ150. The Building Agency only specify Zinalume coatings for buildings with Exposure Zone of B and C to achieve the durability requirement specified in NZBC Clause B2. In addition, as outlined on NZBC E2/AS1 Table 20, hidden elements coated with AZ150 can achieve 50-year durability. Fixings of galvanised support battens rails must achieve >35mm embedment into main structure.

Refer to Appendix A Fixing Tables 3 & 5

### Design Responsibility

It is expected that the architect/specifier's design intent and specifications (including specified materials, & compatibility where items are subject to material run-off affecting durability) where applicable have been reviewed against the New Zealand Building Code. AliClad Max System, when correctly specified will comply to or contribute to compliance to the following NZBC Clauses and their listed performance clauses as listed.



**MATERIALS • SYSTEMS • SOLUTIONS**

## APPENDIX A - SPAN TABLES


*Table 1: Vertically Aligned - Installed on Timber or Plastic Batten*

WIND ZONE	ALICLAD MAX TYPE				
	V136	V200	S150	S200	S125/75
	MAXIMUM ALLOWABLE SPAN (mm)				
LOW 00m/s-32m/s   <0.6kPa	2200	2200	2200	2200	2200
MEDIUM 32m/s-37m/s   >0.66kPa & <0.88kPa	2000	2000	2000	2000	2000
HIGH 37m/s-44m/s   >0.88kPa & <1.25kPa	1800	1800	1800	1800	1800
VERY HIGH 44m/s-50m/s   >1.25kPa & <1.61kPa	1600	1600	1600	1600	1600
EXTRA HIGH 50m/s-55m/s   >1.61kPa & <1.9kPa	1400	1400	1400	1400	1400
SPECIFIC ENGINEERING DESIGN >55m/s   >1.9kPa	SED	SED	SED	SED	SED

1. SS304 12g x 65mm HexTek Screw 10mm Hex (35mm minimum embedment), screw fixing at every AliClad Max board.  
 2. Table is applicable for non-structural H3.1 Timber and Extruded Plastic cavity packer battens either of which form a nominal 20mm cavity  
 3. Wind Zone Classifications - ULS From NZS3604, considered in Positive(+) Pressure and Negative(-) Suction

*\* Design Assumptions:*

- The wind pressures are for external wind only. Internal pressures will not be applied to the cladding and assumed to be resisted by the internal lining.
- Load on each panel is uniformly distributed.
- The span/deflection limit for SLS wind load is 250mm for aluminium battens/zincalume top hats and L/175 for the AliClad Max boards, with the serviceability wind load equal to 68% of the ULS wind load.
- SS304 12g x 65mm HexTek SD Screw 10mm Hex (AliClad board to Timber Batten)
- Timber is assumed Radiata Pine (Group J4 for withdrawal, group 5 in shear, with a characteristic density in excess of 420kg/m<sup>3</sup>).
  - Timber studs at 600mm o/c and
  - timber nog/dwangs at 800mm o/c and
- For Edge Distances Framing fixing face thickness is assumed as 45mm



**Selected Building Flexible Membrane/RAB/RWU must be compliant to E2:Table 23**

**Fixings for Vertical Timber Batten @ Each Nog = 800mm MAX C/C or less as appropriate to site wind zone & bracing requirements in accordance with NZS3604**

# ALICLAD MAX

## PARTS LIST

### CLADDING PROFILES

- ACV136** - AliClad Max V136, 136x25 V Shiplap Weatherboard, 5.8m.  
**ACV200** - AliClad Max V200, 200x25 V Shiplap Weatherboard, 5.8m.  
**ACS150** - AliClad Max S150, 150x25 Shadow Groove Weatherboard, 5.8m.  
**ACS200** - AliClad Max S200, 200x25 Shadow Groove Weatherboard, 5.8m.  
**ACS125/75** - AliClad Max S200-125/75, 200x25 Shadow Groove Weatherboard with 75mm & 125mm board look, 5.8m.

### 2 PIECE BASE CLIPS

- ACHMDB-58** AliClad Max - H Mould Base, 5.8m.  
**ACJMDB-58** AliClad Max - J-Mould Base, 5.8m.  
**ACJMDF-58** AliClad Max - J-Mould Face, 5.8m, Selected Finish.  
**ACINTB-58** AliClad Max - Internal Corner Base, 5.8m, Selected Finish.  
**ACEXTB-58** AliClad Max - External Corner Base, 5.8m.  
**ACJMDBC-58** AliClad Max - Bottom of Cladding Base, 5.8m, Selected Finish.

### 2 PIECE FACES & TRIMS

- ACINTF** - AliClad Max - Internal Corner Face, 5.8m.  
**ACWNS** - AliClad Max - Window Sill Face, - to suit WANZ supported window, 5.8m, Selected Finish.  
**ACWNSP** - AliClad Max - Window Sill Face - to suit Punched Window, 5.8m, Selected Finish.  
**ACJMDF** - AliClad Max - J Mould Face, 5.8m, Selected Finish.  
**ACHMDF** - AliClad Max - H Mould Face, 5.8m, Selected Finish.  
**ACEXTF** - AliClad Max - External Corner Face, 5.8m, Selected Finish.

### JUNCTION ELEMENTS

- ACCLZ-58** AliClad Max - Clamp Zed, 5.8m, Selected Finish.  
**ACCLC-58** AliClad Max - Clamp Channel, 5.8m, Mill Finish.  
**ACSTR-58** AliClad Max - Starter Rail, 5.8m, Mill Finish.  
**ACJMC-58** AliClad Max - Jamb Clip, 5.8m, Mill Finish.  
**ACJMF-58** AliClad Max - Jamb Flashing, 5.8m, Selected Finish.

### MECHANICAL DRAINAGE SYSTEM

- ACJMT-01RIGHT** AliClad Max - Type 1a Jamb Tray Right  
**ACJMT-01LEFT** AliClad Max - Type 1b Jamb Tray Left  
**ACJMT-02RIGHT** AliClad Max - Type 2a Jamb Tray Right  
**ACJMT-02LEFT** AliClad Max - Type 2b Jamb Tray Left

### ALPHA RAIL SUPPORT SYSTEM PROFILES

- AR-CLIP100** Alpha Rail Packer Clip 10mm, 50mm.  
**AR-CLIP50** Alpha Rail Packer Clip 5mm, 50mm.  
**AR-CLIP30** Alpha Rail Packer Clip 3mm, 50mm.  
**AR-CLIP16** Alpha Rail Packer Clip 1.6mm, 50mm.  
**AR-RAIL20H** Alpha Rail Vertical Rail 20mm, 5.8m.  
**AR-RAIL20V** Alpha Rail Horizontal Rail 20mm, Drained, 5.8m.

AliClad Max - Parts List

Detail Number

AC-V-TB-PL

Version

[v2.2]



**MATERIALS • SYSTEMS • SOLUTIONS**


# ALICLAD MAX

## CLADDING PROFILES


HIGH PERFORMANCE ALUMINIUM  
WEATHERBOARD SYSTEM

2.1


VI36




V200




SI50



S200



SI25-75



# V

≡ - GROOVE

# S

□ - GROOVE

Cladding Profiles

Detail Number

AC-V-TB-PRO-01

Version

[v2.2]

**BA** THE  
BUILDING  
AGENCY


**MATERIALS • SYSTEMS • SOLUTIONS**

# ALICLAD MAX


## TRIMS - PROFILES

### TYPICAL ASSEMBLIES


#### J-MOULD




#### WANZ WINDOW SILL




#### PUNCHED WINDOW SILL




#### TYPICAL BASE OF CLADDING




#### TYPICAL JAMB




#### STARTER




#### ENDER




#### TYPICAL VERTICAL H-JOINT



#### EXTERNAL CORNER



#### INTERNAL CORNER



Accessories

Detail Number

AC-V-TB-PRO-02

Version

[v2.2]



MATERIALS • SYSTEMS • SOLUTIONS


# ALICLAD MAX

## MECHANICAL DRAINAGE SYSTEM

PROPRIETARY JAMB-TO-SILL DRAINAGE CLIPS  
- AVAILABLE IN WHITE, GREY AND BLACK.


### TYPE I - FOR WINDOWS USING WANZ BAR SUPPORT

ACJMT-01LEFT -  
Type 1 Jamb Tray Left




SECTION

4.11a





PLAN

ACJMT-01RIGHT -  
Type 1 Jamb Tray Right




4.11b




### TYPE II - FOR PUNCHED OR RECESSED WINDOWS

ACJMT-02LEFT -  
Type 2 Jamb Tray Left




SECTION

4.12b





PLAN

ACJMT-02RIGHT -  
Type 2 Jamb Tray Right



4.12a



Mechanical Drainage System

Detail Number

AC-V-TB-ACC-01

Version

[v2.2]



MATERIALS • SYSTEMS • SOLUTIONS


## VENTILATED CAVITY H3.1 TIMBER BATTENS

ALL HORIZONTALS  
45X20MM DUAL BEVEL/DUAL CASTELLATION




Top View

3.1




Side View




3D

ALL VERTICALS  
45X20MM SQUARE



Top View

3.2



3D

Timber Batten

Detail Number



AC-V-TB-ACC-02

Version

[v2.1]

# ALICLAD MAX


## PROCESSING - RIPPED WEATHERBOARD TERMINATION



Common location for  
termination assembly :  
Into J-Moulds or Corner  
moulds

**ACCLC** - Clamp Channel 100mm  
Clips Fixed with 2x No4-4 Pop  
Rivets to continuous **ACCLZ** at  
800mm MAXIMUM centres &  
100mm MAX from Ends

**Ripped Board Edge Goes  
Here**



General Processing

Detail Number

AC-GP-1


Version

[v2.2]



**MATERIALS • SYSTEMS • SOLUTIONS**

# ALICLAD MAX



NOTE  
ACJMDBC - Drained B.O.C. Base Shown in dashed lines

External Corner


Detail Number  
AC-V-TB-1.1

Version  
[v2.3]



MATERIALS • SYSTEMS • SOLUTIONS

# ALICLAD MAX



NOTE  
ACJMDBC - Drained B.O.C. Base Shown in dashed lines


Internal Corner

Detail Number  
AC-V-TB-1.2  
Version  
[v2.3]



MATERIALS • SYSTEMS • SOLUTIONS

# ALICLAD MAX



**NOTE**  
ACJMDBC - Drained B.O.C. Base Shown in dashed lines

**SEQUENCE OF INSTALLATION**

- 1 45x20mm Castellated Timber Cavity Battens
- 2 External Corner Base
- 3 SS304 12gx65mm HexTek Screw
- 4 Alternate Cladding Exterior

1 Alternate Support Structure

Ext Cnr\_SML Cladding Type


Detail Number \_\_\_\_\_  
Version \_\_\_\_\_  
[v2.1]

AC-V-TB-1.3



**MATERIALS • SYSTEMS • SOLUTIONS**

# ALICLAD MAX



**NOTE 1**  
ACJMDBC - Drained B.O.C. Base Shown in dashed lines

**NOTE 2**  
Flashings and Angles are not included in the system



Int Cnr\_SML Cladding Type


Detail Number  
AC-V-TB-1.4

Version  
[v2.3]



**MATERIALS • SYSTEMS • SOLUTIONS**

# ALICLAD MAX



NOTE  
ACJMDBC - Drained B.O.C. Base Shown in dashed lines

Vert. Joint\_Typical


Detail Number  
AC-V-TB-2.1

Version  
[v2.3]



MATERIALS • SYSTEMS • SOLUTIONS

# ALICLAD MAX



NOTE 1  
ACJMDBC - Drained B.O.C. Base Shown in dashed lines

NOTE 2  
Additional Framing is required at junction of cladding types to ensure adequate fixing

Vert. Joint\_Orientation Change

Detail Number \_\_\_\_\_  
AC-V-TB-2.2


Version \_\_\_\_\_

[v2.3]



MATERIALS • SYSTEMS • SOLUTIONS

# ALICLAD MAX



NOTE 1  
ACJMDBC - Drained B.O.C. Base Shown in dashed lines

NOTE 2  
Additional Framing is required at junction of cladding types to ensure adequate fixing

**SEQUENCE OF INSTALLATION**

1 45x20mm Castellated Timber Cavity Battens 1 Alternate Support Structure

2 ACHMDB - H-Mould Base 3 Alternate Cladding Exterior

Vert. Joint\_SML Cladding Type


Detail Number \_\_\_\_\_  
AC-V-TB-2.3

Version \_\_\_\_\_  
[v2.3]



**MATERIALS • SYSTEMS • SOLUTIONS**

# ALICLAD MAX



NOTE 1  
ACJMDBC - Drained B.O.C. Base Shown in dashed lines

NOTE 2  
Additional Framing is required at junction of cladding types to ensure adequate fixing

NOTE 3  
Flashings and Angles are not included in the system

**SEQUENCE OF INSTALLATION**

- 1 45x20mm Castellated Timber Cavity Battens
- 1 Alternate Support Structure
- 2 Alternate Cladding Exterior
- 3 Selected Aluminium Angle **By Others**
- 4 Selected Screw **By Others**

Vert. Joint\_LRG Cladding Type


Detail Number  
AC-V-TB-2.4

Version  
[v2.3]



MATERIALS • SYSTEMS • SOLUTIONS

# ALICLAD MAX



**NOTE 1**  
Flashings and Angles are not included in the system

**NOTE 2**  
Cavity Closures are not included in the system

Detail Number \_\_\_\_\_  
Version \_\_\_\_\_


[v2.3]



**MATERIALS • SYSTEMS • SOLUTIONS**

Hori. Joint\_Typical

# ALICLAD MAX



**NOTE**  
Flashings and Angles are not included in the system


Interstorey Joint

Detail Number \_\_\_\_\_  
AC-V-TB-3.2  
Version \_\_\_\_\_  
[v2.3]



**MATERIALS • SYSTEMS • SOLUTIONS**

# ALICLAD MAX



NOTE 1  
ACJMDBC - Drained B.O.C. Base Shown in dashed lines

NOTE 2  
Additional Framing is required at junction of cladding types to ensure adequate fixing

TOP Cladding\_Parapet


Detail Number  
AC-V-TB-4.1

Version  
[v2.3]



MATERIALS • SYSTEMS • SOLUTIONS

# ALICLAD MAX



**NOTE**  
Cavity Closer are not included in the system

BTM Cladding\_G.L


Detail Number  
AC-V-TB-4.2

Version  
[v2.3]



**MATERIALS • SYSTEMS • SOLUTIONS**

# ALICLAD MAX



BTM Cladding\_ Apron Roof

Detail Number

AC-V-TB-4.4


Version

[v2.3]



**MATERIALS • SYSTEMS • SOLUTIONS**

# ALICLAD MAX



**NOTE**

Weathering membrane under soffit is not required, but is recommendable for air barrier performance when a rigid wind barrier is not in use.  
-By Others

Detail Number

AC-V-TB-4.8

Version


[v2.3]

Top Cladding\_Barge/Fascia Board



**MATERIALS • SYSTEMS • SOLUTIONS**

# ALICLAD MAX



**NOTE**

Weathering membrane under soffit is not required, but is recommendable for air barrier performance when a rigid wind barrier is not in use.  
-By Others

Detail Number

AC-V-TB-5.1

Version


[v2.3]

Wall BLW\_Soffit <math><90^\circ</math>



**MATERIALS • SYSTEMS • SOLUTIONS**

# ALICLAD MAX



**NOTE 1**

Weathering membrane under soffit is not required, but is recommendable for air barrier performance when a rigid wind barrier is not in use. -By Others

**NOTE 2**

Flashings and Angles are not included in the system

Detail Number

AC-V-TB-5.2

Version



[v2.3]

Wall ABV\_Soffit <90°



**MATERIALS • SYSTEMS • SOLUTIONS**

# ALICLAD MAX



OPTION 2

**NOTE 1**  
Weathering membrane under soffit is not required, but is recommendable for air barrier performance when a rigid wind barrier is not in use. -By Others

**NOTE 2**  
Flashings and Angles are not included in the system

Detail Number \_\_\_\_\_  
AC-V-TB-5.6

Version \_\_\_\_\_


Wall BLW\_Flat Sheet Soffit <math>< 90^\circ</math>

[v2.3]



**MATERIALS • SYSTEMS • SOLUTIONS**

# ALICLAD MAX



**NOTE 1**

Weathering membrane under soffit is not required, but is recommendable for air barrier performance when a rigid wind barrier is not in use. -By Others

**NOTE 2**

Flashings and Angles are not included in the system

Detail Number

Wall BLW\_Flat Sheet Soffit >90°

AC-V-TB-5.8

Version

[v2.3]



**MATERIALS • SYSTEMS • SOLUTIONS**

# ALICLAD MAX

Wet Seal Adhesion Tape  
By Others

Sill Tape - 150mm  
By Others

SS304 8gx38mm PH SD  
Screw #2 Sq.Dr

SS304 12gx65mm HexTek  
Screw 10mm Hex

ACJMC - Jamb Clip

Selected Sealant on  
PEF Rod to suit gap By  
Others

ACJMF - Jamb Flashing

Selected E2/AS1 Table 23  
Compliant Membrane  
System By Others

45x20mm Castellated  
Timber Cavity Battens

Packer By Others

Selected Separation  
Barrier By Others

AliClad Max Vertical Shiplap Weatherboard Cladding

ACJMDBC - Drained B.o.C. Base

ACJMDB - J- Mould Base


ACCLC - Clamp Channel

AS73 4-4 Truss Pop Rivet

ACCLZ - Clamp Zed

SS304 8gx19mm PH SD ST Screw #2 Sq Dr

ACJMDF - J- Mould Face



NOTE

ACJMDBC - Drained B.O.C. Base Shown in dashed lines

Detail Number

AC-V-TB-7.1

Version

[v2.3]

Window Jamb\_Recessed



MATERIALS • SYSTEMS • SOLUTIONS

# ALICLAD MAX

Selected E2/AS1 Table 23  
Compliant Membrane  
System **By Others**

45x20mm Castellated  
Timber Cavity Battens

AliClad Max Vertical Shiplap  
Weatherboard Cladding

Selected Separation  
Barrier **By Others**

SS304 12x65mm HexTek Screw  
10mm Hex

Selected Flashing Tape -  
60mm **By Others**

Selected Screw **By Others**


ACJMDBC - Bottom of  
Cladding Base

ACJMDF - J- Mould Face

Al. 1.6mm Custom Folded **By Others**

Sill Tape - 150mm **By Others**

Wet Seal Adhesion Tape **By Others**



**NOTE 1**

Refer to drawing "7.1" for Sill/Jamb Junction

**NOTE 2**

Flashings and Angles are not included in the system

Detail Number

AC-V-TB-7.2

Version


[v2.3]

Window Head\_Recessed



**MATERIALS • SYSTEMS • SOLUTIONS**

# ALICLAD MAX



NOTE  
Refer to drawing "7.1" for Sill/Jamb Junction

Window Sill\_Recessed


Detail Number  
AC-V-TB-7.3  
Version

[v2.3]



MATERIALS • SYSTEMS • SOLUTIONS

# ALICLAD MAX



**NOTE**  
ACJMDBC - Drained B.O.C. Base Shown in dashed lines

Window Jamb\_WANZ/Supported

Detail Number \_\_\_\_\_  
AC-V-TB-7.4

Version \_\_\_\_\_

[v2.3]



**MATERIALS • SYSTEMS • SOLUTIONS**

# ALICLAD MAX

Selected E2/AS1 Table 23 Compliant Membrane System **By Others**

45x20mm Castellated Timber Cavity Battens

Selected Separation Barrier **By Others**

AliClad Max Vertical Shiplap Weatherboard Cladding

SS304 12gx65mm HexTek Screw 10mm Hex

Selected Flashing Tape - 60mm

Selected Screw **By Others**


ACJMDBC - Bottom of Cladding Base

ACJMDF - J- Mould Face

Al. 1.6mm Custom Folded **By Others**

Sill Tape - 150mm **By Others**

Wet Seal Adhesion Tape **By Others**



**NOTE 1**

Refer to drawing "7.4" for Sill/Jamb Junction

**NOTE 2**

Flashings and Angles are not included in the system

Detail Number

AC-V-TB-7.5

Version


[v2.3]

Window Head\_WANZ/Supported



MATERIALS • SYSTEMS • SOLUTIONS

# ALICLAD MAX



**NOTE**

Refer to drawing "7.4" for Sill/Jamb Junction

Detail Number

AC-V-TB-7.6

Version


[v2.3]

Window Sill\_WANZ/Supported



MATERIALS • SYSTEMS • SOLUTIONS

# ALICLAD MAX



NOTE  
ACJMDBC - Drained B.O.C. Base Shown in dashed lines



Window Jamb\_Recessed

Detail Number  
AC-V-TB-7.7

Version  
[v2.3]



MATERIALS • SYSTEMS • SOLUTIONS

# ALICLAD MAX

Selected E2/AS1 Table 23 Compliant Membrane System **By Others**

45x20mm Castellated Timber Cavity Battens

Selected Separation Barrier **By Others**

AliClad max Vertical Shiplap Weatherboard Cladding

SS304 12gx65mm HexTek Screw 10mm Hex

Selected Flashing Tape - 60mm **By Others**

Selected Screw **By Others**


ACJMDBC - Bottom of Cladding Base

ACJMDF - J- Mould Face

Al. 1.6mm Custom Folded **By Others**


Sill Tape - 150mm **By Others**

Wet Seal Adhesion Tape **By Others**



**NOTE 1**  
Refer to drawing "7.7" for Sill/Jamb Junction

**NOTE 2**  
Flashings and Angles are not included in the system



Window Head\_Recessed


Detail Number \_\_\_\_\_  
AC-V-TB-7.8

Version \_\_\_\_\_  
[v2.3]




**MATERIALS • SYSTEMS • SOLUTIONS**

# ALICLAD MAX



NOTE  
Refer to drawing "7.7" for Sill/Jamb Junction



Window Sill\_Recessed

Detail Number

AC-V-TB-7.9


Version

[v2.3]



MATERIALS • SYSTEMS • SOLUTIONS

# ALICLAD MAX



## INSTALLATION SEQUENCE

Detail Number

AC-V-TB-8.0


Version

[v2.3]



**MATERIALS • SYSTEMS • SOLUTIONS**

# ALICLAD MAX



**NOTE**  
ACJMDBC - Drained B.O.C. Base Shown in dashed lines

Door Jamb\_Recessed

Detail Number  
AC-V-TB-8.1

Version

[v2.3]



**MATERIALS • SYSTEMS • SOLUTIONS**

# ALICLAD MAX

Selected E2/AS1 Table 23 Compliant Membrane System **By Others**

Selected Separation Barrier **By Others**

45x20mm Castellated Timber Cavity Battens

AliClad Max Vertical Shiplap Weatherboard Cladding

SS304 12gx65mm HexTek Screw 10mm Hex

Selected Flashing Tape - 60mm **By Others**

Selected Screw **By Others**


ACJMDBC - Bottom of Cladding Base

ACJMDF - J- Mould Face

Al. 1.6mm Custom Folded **By Others**

Sill Tape - 150mm **By Others**


Wet Seal Adhesion Tape **By Others**



Sill Tape - 150mm **By Others**

Al. 1.2mm Custom Folded **By Others**

Selected E2/AS1 Table 23 Compliant Membrane System **By Others**



NOTE 1

Refer to drawing "8.1" for Sill/Jamb Junction

NOTE 2

Flashings and Angles are not included in the system

Detail Number

AC-V-TB-8.2

Version

[v2.3]

Door Head & Sill Recessed



MATERIALS • SYSTEMS • SOLUTIONS

# ALICLAD MAX



INSTALLATION SEQUENCE

Detail Number

AC-V-TB-8.3


Version

[v2.3]




**MATERIALS • SYSTEMS • SOLUTIONS**

# ALICLAD MAX



**NOTE**  
ACJMDBC - Drained B.O.C. Base Shown in dashed lines



Window Jamb\_Corner

Detail Number  
AC-V-TB-8.4


Version

[v2.3]



**MATERIALS • SYSTEMS • SOLUTIONS**

# ALICLAD MAX



**NOTE**  
ACJMDBC - Drained B.O.C. Base Shown in dashed lines



Window Jamb\_Corner Above & Under Window

Detail Number \_\_\_\_\_  
Version \_\_\_\_\_


AC-V-TB-8.5

[v2.3]



**MATERIALS • SYSTEMS • SOLUTIONS**

# ALICLAD MAX



Internal Corner to Window Jamb

Detail Number

AC-V-TB-8.6

Version

[v2.3]



**MATERIALS • SYSTEMS • SOLUTIONS**